

## LIGHT TECHNOLOGY

LED


<b>System Power:</b>	41W
<b>Colour Temperature:</b>	4000K
<b>Luminous Flux:</b>	4955Lm
<b>Colour Rendering Index (CRI):</b>	>80
<b>Luminaire Efficiency:</b>	120.85Lm/W
<b>Light Distribution:</b>	Direct 90°
<b>Weight:</b>	3.1Kg
<b>Protection rating. Class:</b>	IP20/40 , II
<b>Colour:</b>	White
<b>Dimensions:</b>	L:596 x W:596 x H:34mm
<b>Gear:</b>	ON/OFF



## DETAILS

### APPLICATION

Office Lighting



## MANUFACTURER

**LUXIONA**

## COUNTRY OF ORIGIN

**SPAIN**

## BACKPANEL LED 5800

Modern LED panel dedicated to be mounted on suspended modular ceilings, cardboard suspended ceilings (using adaptive frame), directly on the ceiling (using adaptive frame) or using adaptive frame and suspensions. Equipped with the highly efficient LED sources. Direct light distribution. Luminaire body made from steel sheet. PMMA opal diffuser. Colour of luminaire - white. CRI>80. Luminaire dedicated for the public use structure like offices, conference rooms, classrooms, lecture halls etc.