




| | |
|---|---------------------|
| System Power: | 27 |
| Temperature : | 4000K |
| Luminous flux: | 4000 lm |
| Colour rendering index (CRI): | 80 |
| Luminaire Efficiency: | 148 lm/W |
| Voltage - Frequency: | 220-240V - 50/60 Hz |
| LUMINAIRE-Protection rating . Class: | IP 20, I, IK06 |
| Luminaire Color: | White RAL9016 |
| DIMENSIONS: | 622 x 580 x 92 mm |




DETAILS

APPLICATION

Architectural Lighting
Interior Lighting




ΚΑΤΑΣΚΕΥΑΣΤΗΣ



ΧΩΡΑ ΠΡΟΕΛΕΥΣΗΣ

ΓΕΡΜΑΝΙΑ



BELVISO C1

The Belviso luminaire family represents high quality lighting solutions together with glare-free light and unusual lighting effects. The design of the Belviso Cassette as a pure surface is enlivened by the precisely delineated light contour. The colour-illuminated light frame is available optionally and achieves an emotional upgrading of the lighting design. Five expressive alternatives mean that room-specific or individual colour codings can be selected.

Applications

For innovative, prestigious lighting or auxiliary lighting in retail areas, foyers, corridors, office areas, conference rooms, hotels, restaurants and living spaces.

Mounting methods

Can be universally used in cut-out recess openings and in system ceilings with concealed or exposed grids. Installation in system ceilings with asymmetric, concealed grids on request. For system dimension 625 mm x 625 mm, For ceiling cut-outs 580 mm x 580 mm, Recess depth 330 mm.

