



## LIGHT TECHNOLOGY

LED

<b>System Power:</b>	8W - 16W
<b>Light Colour:</b>	PC / WW / NW / PM / CW
<b>Luminous flux:</b>	up to 1860Lm
<b>Colour rendering index (CRI):</b>	>90
<b>Lighting Distribution:</b>	80° Canopy Lens with White cover
<b>Protection rating. Class:</b>	IP44
<b>Dimensions:</b>	L:630-1200mm

## DETAILS

### APPLICATION

Refrigeration Lighting  
Food Lighting



## MANUFACTURER

# LUMITECH

## COUNTRY OF ORIGIN

### AUSTRIA

## BRIGHT LINEHANDRAIL

Efficient lighting of handrails for cooling and freezer equipment Available in a variety of light colours and can be matched to specific food types Ready-to-connect solution available, thanks to our Cinch Connection System High operational performance due to directional lighting, integrated heat removal and highly efficient LEDs Excellent product illumination thanks to the combination of SMD LEDs and innovative optics Safe-use operation due safety extra-low voltage (SELV) Simple installation with application of fixing plates Heat sink profile made of anodised, extruded aluminium LED modules protected against moisture & dust by Conformal coating End caps made of PBT Linear lenses made of PMMA Dimming capability