



LUMINAIRE TYPE

LINEAR


System Performance:	14W
Temperature:	3000K - 6500K
Luminous Flux:	2000-10000 lm
CRI:	>80
Luminous efficiency:	186-190 lm/W
Lifespan:	70000-90000 hr
Dimensions:	L: 737mm ή 2211 W: 62mm H: 50mm
Weight:	1 Kg
Frequency:	50/60 Hz
Protection:	IP20, IP50
Protection Class:	I



DETAILS

APPLICATION

Food Lighting
Retail Lighting
Architectural Lighting



MANUFACTURER

oktalite

COUNTRY OF ORIGIN



E-Line Next LED

A classic with new technology:

E-LINE NEXT LED impresses with efficient LED technology with up to 190 lm/W and a service life of up to 90,000 hrs. Permanently low operating costs are thus guaranteed. Thanks to the wide range of luminous flux packages, retail areas with high mounting heights can be illuminated just as easily and efficiently as stores with classic room heights.

Ready for the future in 44 seconds:

This is how quickly existing E-Line systems can be changed to the next generation of our classic continuous rooflight - without tools, using click and clip!

A special feature of the E-Line Next LED is the ConVision technology:

The use of lens and light chamber (limiter) enables excellent illumination with best glare control.