



## **LUMINAIRE TYPE**

SEMI-RECESSED

**System Performance:** 

Temperature: 2700 K, 3000 K, -EW, 3100 K - BC, 3500 K, 4000 K,

EC, M, M+F, BF

**Luminous Flux:** 1500 lm - 4000 lm

CRI:

Pan - Tilt: swivels through 15°

**Dimensions:** L: 311mm W:101mm H: 125mm

Material: Die-cast Aluminum

**Protection Class:** IP20, I, II

Voltage - Frequency: 220V-240V, 50-60Hz

Weight: 1.3 kg





**MANUFACTURER** 

**OKTALITE** 

**COUNTRY OF ORIGIN** 



## **DETAILS**

## **APPLICATION**

Retail Lighting



**IDESTO** 

The IDESTO wallwasher range is expanding, and now has a recessed version in addition to IDESTO TRACK for the optimal illumination of walls, graphics or images. The IDESTO recessed version brings a sense of calm to the ceiling appearance. With its low recess depth, and thanks to swivelling of the luminaire head, the spotlight can be used highly flexibly and is particularly suitable for sales areas with suspended ceilings. Now wireless lighting management available for low-installation modernization.

It bathes entire walls in uniform light, creating pleasant general lighting on product display walls, large-area images and even rear wall areas in fresh food counters and bakeries. In combination with accent spotlights from the Oktalite portfolio for setting additional highlights, attractive worlds of light can be created.

IDESTO sets new standards as a wallwasher for retail. The reflector specially designed by Oktalite creates a calm, uniform light without any trapezoidal image on the wall. The softly tapered edges of the light image enable an attractive, uniform light image without shadow gaps even when several wallwashers are arranged next to each other.

Other plus points: IDESTO is easy to install and remove thanks to the Oktalite catch system. And with the swivelling capability of the spotlight head of up to  $15^{\circ}$  in both directions, the light output of the uniform light image on the wall can be easily and individually readjusted.