



LIGHT TECHNOLOGY

LED




System Power:	15W / 23W / 34W / 41W
Colour Temperature:	2700K / 3000K / BeColor 3500K / BeCool 4200K / GoldenBread 2500K / Meat&Fish 4020K / PearlWhite 3100K / SpecialMeat 1900K
Luminous Flux:	up to 4880Lm
Colour Rendering Index (CRI):	>80 / >90
Luminaire Efficiency:	up to 137Lm/W
Beam Angle:	Flood 44° / Medium 25° / NarrowSpot 10° / OvalBasic 40° x 60° / Spot 20° / WallBeam
Rotation Angle/ Swivel Angle:	330° / 90°
Protection Rating	IP20
Class (IP):	
Colour:	Black / Silver / White



DETAILS

APPLICATION

Food Lighting
Retail Lighting
Architectural Lighting



MANUFACTURER

BÄRO
Retail
Lighting

COUNTRY OF ORIGIN

MADE
IN
GERMANY

INTARA IC

With its concave ceiling fitting, the Intara IC luminaire is perfectly integrated in the room. Ceiling mounting, connecting arm and luminaire head with a distinctive, award-winning design form a harmonious unit. The Intara IC semi-recessed luminaires from BÄRO's IC luminaire series received the coveted German Design Award 2020 "Winner" award in the "Excellent Product Design – Lighting" by category. A potentiometer on the ceiling fitting enables simple dimming of the luminaire. The option of customising the length of the arm opens up further application

possibilities.