





LUMINAIRE TYPE

TRACK LIGHT

System Performance: 42W - 92W

Temperature: 2700 K, 3000 K - EW, 3500 K, 4000 K -EC

Luminus Flux: 3000 lm- 5000 lm **Luminous Efficiency:** 60 lm/W - 69 lm/@

CRI: >80 - >90 **Pan Tilt:** 80° swivel

Beam: Oval light distribution

Dimensions: L: 383mm, W: 115mm, H: 153mm

Material: Die-cast aluminium


Frequency: 50-60 Hz
Protection: IP20
Protection Class: I
Weight: 3.2 Kg



DETAILS

APPLICATION

Food Lighting Retail Lighting Architectural Lighting



MANUFACTURER



COUNTRY OF ORIGIN



JUNO TWIN

JUNO TWIN does not only visually make a good impression: the LED twin spotlight works virtually glare-free. The outstanding glare suppression is achieved by the special structure of the back of the lens that already proved successful in Oktalite's patented 3D faceted reflector technology. The luminance on the LED is split up and the light is systematically introduced into the lens – that results in optimum directional lighting control. A defined, harmonious lighting landscape is obtained on the goods in the assortment aisle, in which relaxed shopping is possible.

JUNO TWIN can be equipped with five white light colours and it yields an up to 2×5000 lm strong light output. The twin spotlight unit can be installed in parallel on the power track: that brings calmness to the ceiling layout. The heads, that can be swivelled through up to 40° , have an embossed scale for optimum orientation. The alignment of the light on the goods in the assortment aisle is hence child's play.