



LUMINAIRE TYPE SUSPENDED

System Performance:	21W - 46W
Temperature:	2700 K, 3000 K, - EW, 3100 K - BC, 3500 K, 4000 K, - EC, M, M+F, BF
Luminous Flux:	1500 lm - 5000 lm
CRI:	81 - 97
Luminous Efficiency:	61 - 134.5 lm/W
Dimensions:	D: 500mm Susp. L: 1500mm/3000mm
Material:	Sheet steel
Voltage - Frequency:	220V - 50/60 Hz
Protection Class:	IP20, I

DETAILS

APPLICATION

Food Lighting
Retail Lighting

TYPE


Suspended



Beam angle

Spot


Limba - SP			
Höhe [m]	KegelØ [cm]	E(0°) [lx/klm]	E(C0) [lx/klm]
1	24	6842	3367
2	48	1711	842
3	73	760	374



Beam angle

Flood

Limba - FL			
Höhe [m]	KegelØ [cm]	E(0°) [lx/klm]	E(C0) [lx/klm]
1	66	1981	857
2	132	495	214
3	197	220	95



MANUFACTURER

OKTALITE

COUNTRY OF ORIGIN



LIMBA

With a lampshade in a vintage look, the suspended luminaire LIMBA stands for timeless aesthetics. The custom-selectable performance of the LED modules of up to 5000 lumens in six white light colours provides a wide range of possible uses in every store. For the fresh food area there are three special light colours to choose from.

As an alternative to professional goods illumination, for decorative purposes a filament lamp can be used in the classic lightbulb style. Various cable and shade colours additionally permit customised adaptation to the shop concept. In that way, LIMBA becomes a nostalgic eyecatcher with ultramodern technology.