



## LIGHT TECHNOLOGY

LED

**System Power:**

23W / 34W / 41W / 47W / 59W / 78W

**Light Colour:**

2700K / 3000K / 3500K / 4000K / PearlWhite / Sun / GoldenBread / Fish&Seafood / SpecialMeat

**Luminous flux:**

up to 9750Lm

**Colour rendering index (CRI):**

>80 / >90

**Luminaire Efficiency:**

up to 143Lm/W

**Lighting Distribution:**

Spot 20° / Flood 44° / OvalBasic 40° x 60° / BatWing

**Rotation angle / Swivel angle:**

350° / 120°

**Protection rating. Class:**


IP20 , I

**Color:**

StratoBlack / StratoSilver / Stratowhite / RAL Colours

**Beam:**

BatWing / Flood / OvalBasic / Spot



## DETAILS

### APPLICATION

Food Lighting  
Retail Lighting  
Architectural Lighting



## MANUFACTURER

**BÄRO**  
Retail  
Lighting

## COUNTRY OF ORIGIN

MADE  
IN  
GERMANY

## ONTERO EC 125

Multi-functional and a prize-winning design – that's the Ontero EC surface-mounted luminaire. The design is characterised by flowing transitions from round to angular contours and received an iF design award in 2013. Cooling fins integrated in the luminaire head provide for excellent thermal management, ensuring optimal operating conditions for the LEDs, a long service life and high light quality.