





LIGHT TECHNOLOGY

LED

 System Power:
 15W / 20W / 23W / 28W / 30W / 39W / 40W / 44W

 Light Colour:
 2700K / 3000K / 3500K / 4000K / PearlWhite / Sun /

BeCool / BeColor / GoldenBread / Fish&Seafood /

SpecialMeat / FreshMeat

Luminous flux: up to 4330Lm **Colour rendering** >80 / >90

index (CRI):

Efficiency: up to 142Lm/W

Lighting Distribution: NarrowSpot 10°/ Spot 20° / Medium 25°/ Flood 44° /

OvalBasic 40° x 60° / WallBeam / WallWash

Rotation angle/Swivel $330^{\circ} / 90^{\circ}$

angle:

Protection Rating

Class (IP):

Colour: StratoBlack / StratoSilver / Stratowhite / RAL Colours

Beam: Flood / Medium / NarrowSpot / OvalBasic / Spot /

IP20, I

WallBeam / WallWash

DETAILS

APPLICATION

Food Lighting Retail Lighting Architectural Lighting



MANUFACTURER



COUNTRY OF ORIGIN



ONTERO ID

The Ontero ID surface-mounted luminaire boasts a striking design and highly efficient LED lighting technology. The asymmetrical characteristic, the compact dimensions, the high-quality feel and the interplay of materials underline the suitability of Ontero ID as a lighting tool for demanding retail and exhibition lighting.