

PENDIRO IC / Bäro



LIGHT TECHNOLOGY LED

System Power: Light Colour:

Beam:

Luminous flux: Colour rendering index (CRI): Efficiency: Lighting Distribution: Protection rating . Class: Color: 15 / 23 2700K / 3000K / 3500K / PearlWhite / Sun / GoldenBread / Fish&Seafood / SpecialMeat up to 4,330 lm >80

up to 112 lm/W WallWash IP 20 StratoBlack / StratoSilver / Stratowhite / RAL Colours Flood / Medium / NarrowSpot / OvalBasic

DETAILS 90 75 ,185 **APPLICATION** 60° Food Lighting 2,370 Retail Lighting 45% Architectural Lighting 3,555 30° 15° cd.klm Spot ΚΑΤΑΣΚΕΥΑΣΤΗΣ 90 90 75 75 490 345 60° Retail 60° Lighting 980 690 45% 45% ΧΩΡΑ ΠΡΟΕΛΕΥΣΗΣ 1,470 1,035 30° 309 ■MADE 15° 15° ,380 IN Flood cd.klm OvalBasic cd.klm GERMANY

PENDIRO IC

With its unusual and unconventional design Pendiro IC has a distinctive look. The recess reminiscent of a halfpipe is a characteristic feature. Its deliberately different shape is surprising and gives it a light appearance.